

PROPELLER SHAFT & DIFFERENTIAL CARRIER

GI

MA

EM

LC

EC

FE

CL

MT

AT

TF

PD

FA

RA

BR

ST

RS

BT

HA

EL

IDX

SECTION **PD**

MODIFICATION NOTICE:

- Service data and specifications (SDS) have been added for Australia models.

CONTENTS

SERVICE DATA AND SPECIFICATIONS (SDS)	2	Final Drive.....	5
Propeller Shaft	2		

SERVICE DATA AND SPECIFICATIONS (SDS)

Propeller Shaft

GENERAL SPECIFICATIONS

4WD models (For Australia)

Location		Front			Rear		
Applied model		KA24DE	QD32	ZD30DDTi	KA24DE	QD32	ZD30DDTi
		Long wheelbase					
		M/T	M/T, A/T	M/T		M/T, A/T	M/T
Propeller shaft model		2F63H		2F71H	3S71H	3S80B	
Number of joints		2			3		
Coupling type with transfer		Flange type			Sleeve type		
Type of journal bearing		Solid type (disassembly type)			Solid type (disassembly type)		
Type length (Spider to spider) mm (in)	1st	546 (21.50)	565 (22.24)		392 (15.43)	372 (14.65)	
	2nd	—			870 (34.25)	872 (34.33)	
Shaft outer diameter mm (in)	1st	50.8 (2.00)			75 (2.95)	65 (2.56)	
	2nd	—			65 (2.56)		

2WD models (For Australia)

Applied model		KA24DE				TD27		YD25DDTi		
		Long wheelbase								
		M/T		A/T		M/T				
Propeller shaft model		Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS	4WD appearance
		Standard	Option	Standard	Option	Standard	Option	Standard	Option	
		3S71H						3S80B		
Number of joints		3								
Coupling type with trans- mission		Sleeve type								
Type of journal bearing		Solid type (disassembly type)								
Type length (Spider to spider) mm (in)	1st	641 (25.24)		541 (21.30)		641 (25.24)		642 (25.28)		667 (26.26)
	2nd	1,004 (39.53)	978 (38.50)	1,004 (39.53)	978 (38.50)	1,004 (39.53)	978 (38.50)	1,005 (39.57)	979 (38.54)	984 (38.74)
Shaft outer diameter mm (in)	1st	75 (2.95)						65 (2.56)		75 (2.95)
	2nd	65 (2.56)								

SERVICE DATA AND SPECIFICATIONS (SDS)

Propeller Shaft (Cont'd)

4WD models (For Europe)

Location		Front		Rear	
Applied model		KA24DE	YD25DDTi	KA24DE	YD25DDTi
		Long wheelbase			
		M/T			
Propeller shaft model		2F63H	2F71H	3S71H	3S80B
Number of joints		2		3	
Coupling type with transmission		Flange type		Sleeve type	
Type of journal bearing		Solid type (disassembly type)			
Type length (Spider to spider) mm (in)	1st	546 (21.50)	565 (22.24)	392 (15.43)	372 (14.65)
	2nd	—		870 (34.25)	872 (34.33)*1 847 (33.35)*2
Shaft outer diameter mm (in)	1st	50.8 (2.00)		75 (2.95)	65 (2.56)
	2nd	—		65 (2.56)	

*1: With C200 final drive

*2: With H233B final drive

2WD models (For Europe)

Applied model	KA24DE		YD25DDTi			
	Long wheelbase					
	M/T					
Propeller shaft model	Without ABS	With ABS	Without ABS	With ABS	4WD appearance	
	Standard	Option	Standard	Option		
	3S71H		3S80B			
Number of joints	3					
Coupling type with transmission	Sleeve type					
Type of journal bearing	Solid type (disassembly type)					
Type length (Spider to spider) mm (in)	1st	641 (25.24)		642 (25.28)		667 (26.26)
	2nd	1,004 (39.53)	978 (38.50)	1,005 (39.57)	979 (38.54)	984 (38.74)
Shaft outer diameter mm (in)	1st	75 (2.95)		65 (2.56)		75 (2.95)
	2nd	65 (2.56)				

SERVICE DATA AND SPECIFICATIONS (SDS)

Propeller Shaft (Cont'd)

4WD models (For the Middle East)

Location		Front	Rear
Applied model		KA24DE	
		Long wheelbase	
		M/T	
Propeller shaft model		2F63H	3S71H
Number of joints		2	3
Coupling type with transmission		Flange type	Sleeve type
Type of journal bearing		Solid type (disassembly type)	
Type length (Spider to spider) mm (in)	1st shaft	546 (21.50)	392 (15.43)
	2nd shaft	—	870 (34.25)
Shaft outer diameter mm (in)	1st shaft	50.8 (2.00)	75 (2.95)
	2nd shaft	—	65 (2.56)

2WD models (For the Middle East)

Applied model		KA24DE						TD27			
		Short wheelbase		Long wheelbase				Short wheelbase		Long wheelbase	
		M/T				A/T		M/T			
Propeller shaft model		Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS
		Standard	Option	Standard	Option	Standard	Option	Standard	Option	Standard	Option
		3S71H									
Number of joints		3									
Coupling type with transmission		Sleeve type									
Type of journal bearing		Solid type (disassembly type)									
Type length (Spider to spider) mm (in)	1st shaft	641 (25.24)				541 (21.30)		641 (25.24)			
	2nd shaft	704 (27.72)	678 (26.69)	1,004 (39.53)	978 (38.50)	1,004 (39.53)	978 (38.50)	704 (27.72)	678 (26.69)	1,004 (39.53)	978 (38.50)
Shaft outer diameter mm (in)	1st shaft	75 (2.95)									
	2nd shaft	65 (2.56)									

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive

GENERAL SPECIFICATIONS

4WD models (For Australia)

Applied model	KA24DE			QD32			ZD30DDTi					
	Single cab, Double cab						Single cab, Double cab, King cab					
	M/T			M/T, A/T			M/T					
Front final drive model	R180A											
Gear ratio	4.625						4.375					
Number of teeth (Drive gear / Drive pinion)	37/8						35/8					
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)											
Rear final drive model	Without ABS		With ABS		Without ABS		With ABS		Without ABS		With ABS	
	Stan- dard	Option			Stan- dard	Option			Stan- dard	Option		
	C200											
	2-Pinion	LSD		2-Pinion		LSD		2-Pinion		LSD		2-Pinion
Gear ratio	4.625						4.375					
Number of teeth (Drive gear / Drive pinion)	37/8						35/8					
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)											

2WD models (For Australia)

Applied model	KA24DE						TD27					
	Single cab, Double cab			Double cab			Single cab, Double cab					
	M/T			A/T			M/T					
Rear final drive model	Without ABS		With ABS		Without ABS		With ABS		Without ABS		With ABS	
	Stan- dard	Option			Stan- dard	Option			Stan- dard	Option		
	C200											
	2-Pinion	LSD		2-Pinion		LSD		2-Pinion	2-Pinion	LSD		2-Pinion
Gear ratio	4.111				4.375				4.111			
Number of teeth (Drive gear / Drive pinion)	37/9				35/8				37/9			
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)											

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive (Cont'd)

Applied model	YD25DDTi						
	Single cab, Double cab				Double cab		
	M/T						
Rear final drive model	Without ABS		With ABS		4WD appearance		
					Without ABS		With ABS
	Standard	Option		Standard	Option		
	C200						
	2-Pinion	LSD		2-Pinion	2-Pinion	LSD	
Gear ratio	3.900				4.625		
Number of teeth (Drive gear / Drive pinion)	39/10				37/8		
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)						

4WD models (For Europe)

Applied model	YD25DDTi									KA24DE		
	Single cab			King cab		Double cab				King cab		
Front final drive model	R180A											
Gear ratio	4.625											
Number of teeth (Drive gear / Drive pinion)	37/8											
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)											
Rear final drive model	Without ABS			With ABS	Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS	Without ABS	With ABS
	Standard		Option		Standard	Option	Standard		Option		Standard	Option
	C200							H233B*		C200		
	4-Pinion	LSD										
Gear ratio	4.625											
Number of teeth (Drive gear / Drive pinion)	37/8											
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)							2.4 (4-1/4)		1.3 (2-1/4)		

*: Patrol car

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive (Cont'd)

2WD models (For Europe)

Applied model	YD25DDTi											GI		
	Single cab			King cab				Double cab						
Rear final drive model	Without ABS		With ABS	With-out ABS	With ABS	4WD appear- ance		Without ABS	With ABS	4WD appear- ance		MA		
						With-out ABS	With ABS			With-out ABS	With ABS	EM		
	Standard	Option		Stan- dard	Option	Stan- dard	Option	Stan- dard	Option		Stan- dard	Option	LC	
	C200													
	2-Pin- ion	LSD		4-Pin- ion	LSD				2-Pin- ion	LSD	4-Pin- ion	LSD	EC	
Gear ratio	3.900					4.625		3.900				4.625		
Number of teeth (Drive gear / Drive pinion)	39/10					37/8		39/10				37/8		FE
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)												CL	

Applied model	KA24DE				MT
	Single cab		King cab		
Rear final drive model	Without ABS	With ABS	Without ABS	With ABS	AT
	Standard	Option	Standard	Option	
	LSD				TF
Gear ratio	4.110				
Number of teeth (Drive gear / Drive pinion)	37/9				PD
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)				FA

4WD models (For the Middle East)

Applied model	KA24DE		BR
	Single cab		
Front final drive model	R180A		ST
Gear ratio	4.625		
Number of teeth (Drive gear / Drive pinion)	37/8		RS
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)		
Rear final drive model	Without ABS	With ABS	BT
	Standard	Option	
	C200		HA
	4-Pinion		
Gear ratio	4.625		EL
Number of teeth (Drive gear / Drive pinion)	37/8		
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)		

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive (Cont'd)

2WD models (For the Middle East)

Applied model	KA24DE						TD27	
	Single cab							
	M/T				A/T		M/T	
Rear final drive model	Without ABS		With ABS		Without ABS	With ABS	Without ABS	With ABS
	Standard	Option			Standard	Option	Standard	Option
	C200							
	2-Pinion		4-Pinion		2-Pinion			
Gear ratio	4.111	4.625	4.111	4.625	4.375		4.111	
Number of teeth (Drive gear / Drive pinion)	37/9	37/8	37/9	37/8	35/8		37/9	
Oil capacity (Approx.) ℓ (Imp pt)	1.3 (2-1/4)							